## **CLAIMS**

I claim:

1. (Currently amended) A device for the rapid consumption of the <u>a</u> combustible load (8) found within reach of a fire, in addition to the <u>and</u> smoke and hot gases (9) and (10) produced by the <u>said</u> fire, taking advantage of the <u>an</u> air chamber to establish depressions that rapidly consume the <u>consuming said</u> combustible load found within reach of the <u>said</u> fire, using the <u>a</u> chimney effect of natural methods or conventional systems. It is made up of, the device comprising:

an outside façade sheet (2) of reinforced concrete, ceramic material or any other fire-resistant material, and;

an inside façade sheet—(3) of reinforced concrete, ceramic material or any other fire-resistant material. Between the;

an air chamber between said outside façade (2) sheet and said inside façade (3) there is an air chamber (4), in addition to sheet; and

a chimney (5) or depression chamber, which is connected to the <u>said air</u> chamber (4) and <u>has having</u> an entrance (5) connected to the <u>a</u> conduct (5) and the air chamber (4). There is also <u>, wherein said chimney has</u> an exit (7) or union with the <u>air chamber (4) connected</u> to which the <u>said chimney (5) is connected</u>, the <u>said chimney having a mouth (6) of which has with</u> an entrance (11) from the <u>an</u> outside found on the <u>said outside façade</u> sheet (2) of the façade, and in agreement with each of the floors floor separated by the wrought iron (1).

2. (Currently amended) A device for the rapid consumption of the combustible load found within reach of a fire, in addition to the smoke and hot gases produced by the fire, according to the first claim, characterised by Claim 1, further comprising:

an independent air chamber (12).

## \*Marked Up Copy\*

3. (Currently amended) A device for the rapid consumption of the combustible load found within reach of a fire, in addition to the smoke and hot gases produced by the fire, according to the previous two claims, characterised by the possibility of Claim 1, being incorporated in either the a front façade or, back façade, on the sides, and also in the wells of a building, surrounding the a perimeter of the said building to be protected.